

Datasheet

[Get a Quote](#)

Overview

CloudEngine S2730S-S series switches are based on next-generation high-performance hardware and Huawei's unified VRP (Versatile Routing Platform) software platform. Flexible Ethernet networking, various security controls, etc., support a variety of Layer 3 routing protocols, with higher performance and richer business processing capabilities, widely used in enterprise parks area access, 100M, Gigabit to desktop and other application scenarios.

Quick Specification

Model	S2730S-S16FT4S-A
Part Number	98011315
Memory (RAM)	512 MB
Flash	512 MB
PoE	Not supported
Dimensions without packaging (H x W x D) [mm(in.)]	Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 220.0 mm (1.72 in. x 17.4 in. x 8.7 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 43.6 mm x 442.0 mm x 227.0 mm (1.72 in. x 17.4 in. x 8.94 in.)
Dimensions with packaging (H x W x D) [mm(in.)]	90.0 mm x 550.0 mm x 360.0 mm (3.54 in. x 21.65 in. x 14.17 in.)
Weight without packaging [kg(lb)]	2.24 kg (4.94 lb)
Weight with packaging [kg(lb)]	3.13 kg (6.9 lb)

Datasheet

Product Details:

The Front Panel:



①	Eight 10/100BASE-TX ports
②	Eight 10/100/1000BASE-T ports
③	Four 1000BASE-X ports
④	One console port
⑤	One PNP button

The Back Panel:



⑥	Ground screw
⑦	Jack for AC power cable locking strap
⑧	AC socket

Get more information:

Do you have any question about the S2730S-S16FT4S-A 98011315?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Part Number	98011315
Model	S2730S-S16FT4S-A
Dimensions without packaging (H x W x D) [mm(in.)]	<p>Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 220.0 mm (1.72 in. x 17.4 in. x 8.7 in.)</p> <p>Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 43.6 mm x 442.0 mm x 227.0 mm (1.72 in. x 17.4 in. x 8.94 in.)</p>

Datasheet

Dimensions with packaging (H x W x D) [mm(in.)]	90.0 mm x 550.0 mm x 360.0 mm (3.54 in. x 21.65 in. x 14.17 in.)
Chassis height [U]	1 U
Weight without packaging [kg(lb)]	2.24 kg (4.94 lb)
Weight with packaging [kg(lb)]	3.13 kg (6.9 lb)
Typical power consumption [W]	22.7 W
Typical heat dissipation [BTU/hour]	77.46 BTU/hour
Maximum power consumption [W]	28.1 W
Maximum heat dissipation [BTU/hour]	95.88 BTU/hour
MTBF [year]	69.03 year
MTTR [hour]	2 hour
Availability	>0.99999
Noise at normal temperature (acoustic power) [dB(A)]	39 dB(A)
Noise at normal temperature (acoustic pressure) [dB(A)]	27.2 dB(A)
Number of card slots	0
Number of power slots	0
Number of fans modules	1
Redundant power supply	Not supported
Long-term operating temperature [°C(°F)]	-5°C to +50°C (23°F to 122°F) at an altitude of 0-1800 m (0-5906 ft.)
Short-term operating temperature [°C(°F)]	Not supported
Restriction on the operating temperature variation rate [°C(°F)]	When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.). The switch cannot be started when the ambient temperature is lower than 0°C (32°F). Only optical modules with a distance of 10 km or less are supported.
Storage temperature [°C(°F)]	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity [RH]	5% to 95%, noncondensing
Long-term operating altitude [m(ft.)]	0-5000 m (0-16404 ft.)
Storage altitude [m(ft.)]	0-5000 m (0-16404 ft.)
Power supply mode	AC built-in
Rated input voltage [V]	AC input: 100 V AC to 240 V AC, 50/60 Hz
Input voltage range [V]	AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz
Maximum input current [A]	0.8 A
Memory	512 MB
Flash memory	512 MB
Console port	RJ45
Eth Management port	Not supported

Datasheet

USB	Not supported
RTC	Not supported
RPS input	Not supported
Service port surge protection [kV]	Common mode: ± 7 kV
Power supply surge protection [kV]	± 6 kV in differential mode, ± 6 kV in common mode
Types of fans	Built-in
Heat dissipation mode	Heat dissipation with fan, intelligent fan speed adjustment
Airflow direction	Air intake from left and front, air exhaustion from right
PoE	Not supported
Certification	EMC certification Safety certification Manufacturing certification

Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network

[Search](#) our Resource Library

[Follow](#) us on LinkedIn

 Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

 Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

